

Product Description

Traditional woodoil for new treatment and maintenance of wooden decking, garden furniture and the like. In pressure-treated wood and hard woods.

Wood oil has a good penetration into the wood and creates a water repellent surface that stabilizes and prevents shrinkage cracks in the wood.

Contains active UV filter against the sun's harmful rays and special water-repellent waxes.

Contains materials, that protect the film against surface mold.

Directions for use

The wood must be clean, dry and stable. The humidity of the wood should never exceed 18%. The substrate must also be sucking and without previous treatments of varnish, paint and the like.

Weathered wood such as Spruce, Pine and Larch must be cleaned with appropriate cleaner.

Weathered hardwood such as Teak, Mahogany, and the like sanded to fresh wood.

Contaminated surfaces must clean with appropriate cleaner.

Apply the Wood oil with a sponge, brush or roller. Repeat the treatment until the wood appears uniformly and saturated, however, without forming surface film.

Retreatment is usually 1-2 times a year or as needed.

Cleaning instructions

White Spirit or "Brush Cleaner"

Safety & environment

Brush / Roller: Working close, Nitrill-gloves and protective glass and A2 mask.

Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.

Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.

Further information and MSDS on www.bj.dk

Remarks

The product contains non drying oil, meaning waste and tools shall be in a closed container, due to flameability.

Technical data

Binder:	Alkyd and natural oil
Type:	Wood Oil
Gloss:	
Vol. dry:	
Colours:	Colourless
Drying:	6-8 hours, recoatable after 24 hours at 20 ° C 65% RH
Application:	+5° C to +25° C. RF: 40-80%
Thinning:	White Spirit. Should normally not be diluted
Coverage:	5-10 m ² /ltr. Depending on the absorption
Tools:	Brush, cloth or sponge
Mal-Code:	2-1 (1993)

